



10-CODES

- 10.101 - IBC BUILDING TYPES
- 10.110 - FIREBLOCKING
- 10.120 - SEISMIC DESIGN CATEGORIES

20-STEEL FRAMING

- 20.100 - BRACING OPTIONS FOR NON-LOAD BEARING PARTITIONS
- 20.101 - ATTACHMENT OF COLD FORMED STEEL TO CONCRETE STRUCTURES
- 20.110 - LIMITING WALL HEIGHT TABLES
- 20.111 - INSTALLING RESILIENT CHANNEL

30-GYPSUM BOARD

- 30.100 - RECOMMENDED LEVELS OF FINISH
- 30.101 - JUDGING INTERIOR GYPSUM BOARD
- 30.102 - ENVIRONMENTAL CONDITIONS
- 30.103 - APPLICATION OF GYPSUM BOARD
- 30.104 - MOISTURE-DAMAGED GYPSUM BOARD
- 30.105 - JOINT RIDGING (BEADING)
- 30.150 - FINISHING CONCRETE WITH JOINT COMPOUND
- 30.200 - CONTROL JOINT PLACEMENT IN GYPSUM BOARD ASSEMBLIES
- 30.300 - GYPSUM BOARD CORNER BEAD
- 30.400 - GYPSUM BOARD & ADHESIVE TAPE

40-CEILINGS

- 40.101 - INSTALLING ACOUSTICAL LAY-IN TYPE CEILINGS IN SEISMIC REGIONS
- 40.110 - DESIGN DATA FOR SUSPENDED CEILINGS

50-FIRE / SOUND

- 50.102 - CAULKING AND SEALANT INFORMATION
- 50.501 - STC RATINGS & STEEL STUD FRAMED WALLS
- 50.550 - 1/8 INCH VERTICAL GAP FIRE TEST FOR GYPSUM BOARD
- 50.551 - FIRE RATED FIELD CONDITIONS (MISSED FASTENER)
- 50.552 - FIRE RATED FIELD CONDITIONS (TRADE DAMAGE)

60-EXTERIOR PLASTER

- 60.100 - PROCEDURES FOR JUDGING FINISHED PORTLAND CEMENT PLASTER
- 60.101 - CRACKS IN PORTLAND CEMENT PLASTER
- 60.102 - STUCCO PATCHING & REPAIR METHODS IN PORTLAND CEMENT BASED PLASTER
- 60.103 - PLASTER CRACKING ALONG METAL ACCESSORIES
- 60.105 - SMOOTH TROWELED EXTERIOR FINISHES
- 60.110 - THREE-COAT PLASTER/STUCCO OPTIONS
- 60.120 - STUCCO VS. ACRYLIC FINISH
- 60.121 - ACRYLIC FINISHES
- 60.130 - ONE-COAT STUCCO SYSTEMS
- 60.150 - ASSESSING WOOD-BASED SHEATHING
- 60.155 - STRESS RELIEF JOINS IN PORTLAND CEMENT BASED PLASTER
- 60.160 - LATH & PLASTER CONTROL JOINS OVER CONTINUOUS LATH
- 60.170 - MOIST CURING PORTLAND CEMENT PLASTER/STUCCO
- 60.180 - SLUMP CONE TESTING OF PORTLAND CEMENT BASED PLASTER MIXES
- 60.181 - WATER TESTING OF PORTLAND CEMENT BASED PLASTER/STUCCO
- 60.185 - PLASTER MIXES
- 60.186 - ADDITIONS TO PORTLAND CEMENT PLASTER/STUCCO
- 60.190 - CALIBRATION BOX FOR SAND IN PLASTER MIXES
- 60.195 - EFFLORESCENCE
- 60.196 - CLEANING EFFLORESCENCE
- 60.200 - EXTERNAL CORNER REINFORCEMENT
- 60.210 - PORTLAND CEMENT PLASTER APPLIED TO SOLID MASONRY BASES
- 60.215 - WATER-RESISTIVE BARRIERS EXPOSED TO THE ELEMENTS
- 60.216 - PROPERTIES OF WATER-RESISTIVE BARRIERS
- 60.220 - INSTALLING TWO LAYERS OF WATER-RESISTIVE BARRIER
- 60.281 - EXTERIOR STUCCO SOFFITS AND CEILINGS
- 60.282 - USING "RIB LATH" ON CEILINGS/SOFFITS
- 60.300 - FOAM SHAPES
- 60.400 - EIFS DESIGN DATA

70-INTERIOR PLASTER

- 70.101 - GYPSUM LATH BEHIND GYPSUM PLASTER
- 70.112 - GYPSUM PLASTER OVER CONCRETE/MASONRY SUBSTRATES
- 70.200 - WORKING TIMES FOR GYPSUM PLASTER
- 70.400 - VENETIAN PLASTER

80-MATERIAL HANDLING & SAFETY

90-ENERGY CODES

- 90.500 - NATIONAL CLIMATE ZONES & PRESCRIPTIVE U FACTOR ASSEMBLIES
- 90.501 - CALIFORNIA CLIMATE ZONES & PRESCRIPTIVE U FACTOR ASSEMBLIES FOR FRAMED CONSTRUCTION
- 90.502 - CONTINUOUS INSULATION USING RIGID FOAM BOARDS
- 90.503 - ENERGY CODE COMPARISON CHART
- 90.520 - AIR BARRIERS